

In the claims:

1. (currently amended) A method for forming and transmitting a communication including mapping m input bits to 2^m modulation symbols of a two-dimensional symbol constellation, where m is a positive integer greater than or equal to four, the method comprising:

forming a quarter-quadrant constellation of 2^{m-4} modulation symbols that are located in a first quadrant of the two-dimensional signal plane, the quarter-quadrant constellation having one-sixteenth the size of the two-dimensional symbol constellation;

uniquely associating each modulation symbol of the quarter-quadrant constellation with a respective $m-4$ bit label of the m input bits;

forming a quarter constellation of the two-dimensional symbol constellation by adding to the quarter-quadrant constellation three copies of the quarter-quadrant constellation rotated by -90 degrees, 180 degrees, and -270 degrees, respectively, and then displacing the quarter constellation by a shift value Δ such that the symbols coincide with symbols of the ~~desired~~ two-dimensional symbol constellation, wherein the quarter constellation has one-fourth the size of the two-dimensional symbol constellation;

uniquely associating each symbol of the quarter constellation with a respective $m-2$ bit label of the m input bits, wherein $m-4$ bits of the $m-2$ bit label are inherited from the quarter-quadrant constellation and two further bits of the $m-2$ bit label are used to distinguish quarter-quadrants of the quarter constellation;

forming the two-dimensional symbol constellation by adding to the quarter constellation three copies of the quarter constellation rotated by $+90$ degrees, 180 degrees, and $+270$ degrees, respectively; ~~and~~

uniquely associating each symbol of the two-dimensional symbol constellation with an m-bit label, wherein m-2 bits of the m-bit label are inherited from the quarter constellation and two further bits of the m input bits are used to distinguish quarters of the two-dimensional symbol constellation; and

for each of a plurality of groups of m input bits:

mapping each group of m input bits to the two-dimensional symbol constellation to form a communication symbol; and
transmitting the communication symbol.

2. (original) The method of claim 1, wherein of the two further bits of the m-2 bit label used to distinguish quarter-quadrants of the quarter constellation:

a value of [00] corresponds to a first quarter-quadrant of the quarter constellation having the quarter-quadrant constellation;

a value of [01] corresponds to a second quarter-quadrant of the quarter constellation having a quarter-quadrant constellation that has been rotated by -90 degrees;

a value of [11] corresponds to a third quarter-quadrant of the quarter constellation having a quarter-quadrant constellation that has been rotated by 180 degrees; and

a value of [10] corresponds to a fourth quarter-quadrant of the quarter constellation having a quarter-quadrant constellation that has been rotated by -270 degrees.

3. (original) The method of claim 1, wherein of the two further bits of the m input bits used to distinguish quadrants of the two-dimensional symbol constellation:

a value of [00] corresponds to a first quadrant of the two-dimensional symbol constellation having the quarter constellation;

a value of [01] corresponds to a second quadrant of the two-dimensional symbol constellation having a quarter constellation that has been rotated by -90 degrees;

a value of [11] corresponds to a third quadrant of the two-dimensional symbol constellation having a quarter constellation that has been rotated by 180 degrees; and

a value of [10] corresponds to a fourth quadrant of the two-dimensional symbol constellation having a quarter constellation that has been rotated by -270 degrees.

4. (original) The method of claim 1, wherein:

the two-dimensional symbol constellation is a 256-QAM constellation;

the m input bits comprise eight bits $[y^7, y^6, y^5, y^4, y^3, y^2, y^1, y^0]$;

the 2^{m-4} bits are bits $[y^7, y^6, y^4, y^3]$;

the two further bits of the $m-2$ bit label are bits $[y^5, y^2]$; and

the two further bits of the m input bits are bits $[y^1, y^0]$.

5. (original) The method of claim 1, wherein:

the two-dimensional symbol constellation is a 1024-QAM constellation;

the m input bits comprise ten bits $[y^9, y^8, y^7, y^6, y^5, y^4, y^3, y^2, y^1, y^0]$;

the 2^{m-4} bits are bits $[y^9, y^8, y^7, y^5, y^4, y^3]$;

the two further bits of the $m-2$ bit label are bits $[y^6, y^2]$; and

the two further bits of the m input bits are bits $[y^1, y^0]$.

6. (original) The method of claim 1, wherein forming the quarter constellation further comprises repositioning a plurality of quarter constellation symbol positions.

7. (original) The method of claim 6, wherein:
the two-dimensional symbol constellation is a 128 QAM constellation;
the m input bits comprise seven bits $[y^6, y^5, y^4, y^3, y^2, y^1, y^0]$;
the 2^{m-4} bits are bits $[y^6, y^4, y^3]$;
the two further bits of the m-2 bit label are bits $[y^5, y^2]$; and
the two further bits of the m input bits are bits $[y^1, y^0]$.

8. (original) The method of claim 6, wherein:
the two-dimensional symbol constellation is a 512-QAM constellation;
the m input bits comprise eight bits $[y^8, y^7, y^6, y^5, y^4, y^3, y^2, y^1, y^0]$;
the 2^{m-4} bits are bits $[y^8, y^7, y^5, y^4, y^3]$;
the two further bits of the m-2 bit label are bits $[y^6, y^2]$; and
the two further bits of the m input bits are bits $[y^1, y^0]$.

9. (original) The method of claim 1, further comprising forming the m input bits from a plurality of information bits by operating upon the plurality of information bits to form a Forward Error Correction (FEC) frame.

10. (original) The method of claim 9, wherein the FEC frame includes an integer number of trellis groups.

11. (original) The method of claim 9, wherein Reed-Solomon encoding is employed to form the FEC frame.

12. (original) The method of claim 1, further comprising forming the m input bits from a plurality of information bits by:

Forward Error Correction (FEC) coding the plurality of information bits to produce a plurality of FEC blocks;

interleaving and randomizing the plurality of FEC blocks; and

appending a frame synch trailer to the plurality of interleaved and randomized FEC blocks to form a FEC frame.

13. (original) The method of claim 9, wherein the FEC frame includes an integer number of trellis groups.

14. (currently amended) A method for forming and transmitting a communication including mapping m input bits to a two-dimensional symbol constellation, where m is a positive integer greater than or equal to four, the method comprising:

forming a quarter-quadrant constellation of 2^{m-4} modulation symbols;

forming a quarter constellation of the two-dimensional symbol constellation by adding to the quarter-quadrant constellation three copies of the quarter-quadrant constellation rotated by -90 degrees, 180 degrees, and -270 degrees, respectively, and then displacing the constellation by a shift value Δ such that the symbols coincide with symbols of the ~~desired~~ two-dimensional symbol constellation, wherein the quarter constellation has one-fourth the size of the two-dimensional symbol constellation; ~~and~~

forming the two-dimensional symbol constellation by adding to the quarter constellation three copies of the quarter constellation rotated by +90 degrees, 180 degrees, and +270 degrees, respectively; and

for each of a plurality of groups of m input bits:

mapping each group of m input bits to the two-dimensional symbol constellation to form a communication symbol; and

transmitting the communication symbol.

15. (original) The method of claim 14, wherein forming the quarter-quadrant constellation further comprises uniquely associating each symbol of the quarter-quadrant constellation with a respective m-4 bit label of the m input bits.

16. (original) The method of claim 14, wherein forming the quarter constellation further comprises uniquely associating each symbol of the quarter constellation with a respective m-2 bit label of the m input bits, wherein m-4 bits of the m-2 bit label are inherited from the symbols of the quarter-quadrant constellation and two further bits of the m-2 bit label are used to distinguish quarter-quadrants of the quarter constellation.

17. (original) The method of claim 16, wherein of the two further bits of the m-2 bit label used to distinguish quarter-quadrants of the quarter constellation:

a value of [00] corresponds to a quarter-quadrant of the quarter constellation having an unrotated quarter-quadrant constellation;

a value of [01] corresponds to a second quarter-quadrant of the quarter constellation having a quarter-quadrant constellation that has been rotated by -90 degrees;

a value of [11] corresponds to a third quarter-quadrant of the quarter constellation having a quarter-quadrant constellation that has been rotated by 180 degrees; and

a value of [10] corresponds to a fourth quarter-quadrant of the quarter constellation having a quarter-quadrant constellation that has been rotated by -270 degrees.

18. (original) The method of claim 14, wherein forming the two-dimensional symbol constellation further comprises uniquely associating each symbol of the two-dimensional symbol constellation with an m-bit label, wherein m-2 bits of the m-bit label are inherited from the quarter constellation and two further bits of the m input bits are used to distinguish quadrants of the two-dimensional symbol constellation.

19. (original) The method of claim 18, wherein of the two further bits of the m input bits used to distinguish quadrants of the two-dimensional symbol constellation:

a value of [00] corresponds to a first quadrant of the two-dimensional symbol constellation having the quarter constellation;

a value of [01] corresponds to a second quadrant of the two-dimensional symbol constellation having a quarter constellation that has been rotated by -90 degrees;

a value of [11] corresponds to a third quadrant of the two-dimensional symbol constellation having a quarter constellation that has been rotated by 180 degrees; and

a value of [10] corresponds to a fourth quadrant of the two-dimensional symbol constellation having a quarter constellation that has been rotated by -270 degrees.

20. (original) The method of claim 14, further comprising forming the m input bits from a plurality of information bits by operating upon the plurality of information bits to form a Forward Error Correction (FEC) frame.

21. (original) The method of claim 20, wherein the FEC frame includes an integer number of trellis groups.

22. (original) The method of claim 20, wherein Reed-Solomon encoding is employed to form the FEC frame.

23. (original) The method of claim 14, further comprising forming the m input bits from a plurality of information bits by:

Forward Error Correction (FEC) coding the plurality of information bits to produce a plurality of FEC blocks;

interleaving and randomizing the plurality of FEC blocks; and

appending a frame synch trailer to the plurality of interleaved and randomized FEC blocks to form a FEC frame.

24. (original) The method of claim 23, wherein the FEC frame includes an integer number of trellis groups.

25. (currently amended) A transmitter comprising:

Forward Error Correction block that receives a plurality of information bits and that produces a plurality of FEC blocks;

an interleaver that interleaves the plurality of FEC blocks;

a randomizer that randomizes the plurality of FEC blocks;

a frame synch trailer block that appends a frame synch trailer block to the plurality of interleaved and randomized FEC blocks to form an FEC frame having a plurality of input bits; and

an encoder that maps m input bits of the plurality of input bits to a two-dimensional symbol constellation that that was constructed by:

forming a quarter-quadrant constellation of 2^{m-4} modulation symbols, where m is a positive integer greater than or equal to four;

forming a quarter constellation of the two-dimensional symbol constellation by adding to the quarter-quadrant constellation three copies of the quarter-quadrant constellation rotated by -90 degrees, 180 degrees, and -270 degrees, respectively, and then displacing the constellation by a shift value Δ such that the symbols coincide with symbols of the ~~desired~~ two-dimensional symbol constellation, wherein the quarter constellation has one-fourth the size of the two-dimensional symbol constellation; and

forming the two-dimensional symbol constellation by adding to the quarter constellation three copies of the quarter constellation rotated by +90 degrees, 180 degrees, and +270 degrees, respectively.

26. (currently amended) An apparatus for mapping m input bits to 2^m modulation symbols of a two-dimensional symbol constellation, where m is a positive integer greater than or equal to four, the apparatus comprising:

means for forming a quarter-quadrant constellation of 2^{m-4} modulation symbols that are located in a first quadrant of the two-dimensional signal plane, the quarter-quadrant constellation having one-sixteenth the size of the two-dimensional symbol constellation;

means for uniquely associating each modulation symbol of the quarter-quadrant constellation with a respective $m-4$ bit label of the m input bits;

means for forming a quarter constellation of the two-dimensional symbol constellation by adding to the quarter-quadrant constellation three copies of the quarter-quadrant constellation rotated by -90 degrees, 180 degrees, and -270 degrees, respectively, and then displacing the constellation by a shift value Δ such that the symbols coincide with symbols of the ~~desired~~ two-dimensional symbol constellation, wherein the quarter constellation has one-fourth the size of the two-dimensional symbol constellation;

means for uniquely associating each symbol of the quarter constellation with a respective $m-2$ bit label of the m input bits, wherein $m-4$ bits of the $m-2$ bit label are inherited from the quarter-quadrant constellation and two further bits of the $m-2$ bit label are used to distinguish quarter-quadrants of the quarter constellation;

means for forming the two-dimensional symbol constellation by adding to the quarter constellation three copies of the quarter constellation rotated by $+90$ degrees, 180 degrees, and $+270$ degrees, respectively; and

means for uniquely associating each symbol of the two-dimensional symbol constellation with an m -bit label, wherein $m-2$ bits of the m -bit label are inherited from the quarter constellation and two further bits of the m input bits are used to distinguish quarters of the two-dimensional symbol constellation.